

GYLON EPIX® Style 3504

Case Study: Multinational chemical processing



Industry

Chemical

Customer

Multinational Chemical Processor

Background

On glass fiber reinforced process lines, rubber steel gaskets are specified. Chemical attack of the gasket was observed after less than six-months of service. It was at this point that the customer contacted Garlock for assistance in selecting a product that would provide the necessary chemical resistance and a minimum service life of one year to get them through to the next outage.

Challenges faced

Extremely corrosive and toxic media, sulfuric acid and hydrogen peroxide, are being handled. In addition, the customer reported that several of the non-metallic (FRP) flanges were misaligned, which made it difficult to achieve and maintain an effective seal long term.

Operating Conditions

1. Media: 25% sulfuric acid and some hydrogen peroxide
2. Temperature: Ambient
3. Pressure: 2-3 bar
4. Size: DN200 PN10 (8"-150#)"

Solution and Benefits

Two GYLON EPIX® Style 3504 test gaskets were installed and were removed and inspected ten months later at the scheduled outage. The impression of the flanges was clearly visible showing that the gasket conformed to the flange misaligned faces. GYLON EPIX® 3504 showed absolutely no sign of any chemical attack or leakage during the evaluation period.

The previously used metal-rubber gasket may have degraded due to the use of low quality rubber. Garlock GYLON® is a made from premium grade PTFE material to ensure reliable performance.

For more information, please visit:

www.garlock.com

GARLOCK GMBH

an EnPro Industries family of companies

Falkenweg 1, 41468 Neuss, Germany

+49 2131 349 0

garlockgmbh@garlock.com

www.garlock.com

Garlock Sealing Technologies

Garlock USA

Garlock Australia

Garlock Canada

Garlock China

Garlock Germany

Garlock India

Garlock de México

Garlock New Zealand

Garlock Singapore