

# Case Study: Phosphate Processor

## GYLON EPIX™ 3504 EPX



### INDUSTRY

Chemical

### CUSTOMER

Phosphate processor

### BACKGROUND

Pump inlet and discharge flanges

### CHALLENGES FACED

Using glass filled PTFE. The flange surfaces were being filled with epoxy when maintenance assessed the surfaces condition to be undesirable. Plant personnel wanted to do away with the use of epoxy on the flanges.

### CONDITIONS

Applicaton 1 - Sulfuric Acid 99%:

- » Temperature: 104°F (40°C)
- » Equipment: Pump for sulfuric acid transfer
- » Pump discharge, 8", Alloy 20, Class 150 raised face flanges with B7 bolts
- » Pressure: 57 psig (4 kg/cm<sup>2</sup>)

### CONDITIONS CON'T

Applicaton 2 - Phosphoric & Sulfuric Acid 99%:

- » Temperature: 104°F (40°C)
- » Pump discharge, 8", Alloy 20, Class 150 raised face flanges with B7 bolts
- » Pressure: 57 psig (4 kg/cm<sup>2</sup>)

### SOLUTION AND BENEFITS

Through close collaboration with the customer, it was determined that the best solution would be the new GYLON EPIX™ 3504 EPX. Installation of 8" ring gaskets was complete without special handling using the plant's standard practices.

For more information, please visit:  
<http://www.garlock.com>

### GARLOCK

an EnPro Industries family of companies  
Tel: 1-877-GARLOCK / 315.597.4811  
Fax: 800.543.0598 / 315.597.3216  
[www.garlock.com](http://www.garlock.com)

Garlock  
GPT  
Garlock Australia  
Garlock de Canada, LTD

Garlock China  
Garlock Singapore  
Garlock Germany  
Garlock India Private Limited

Garlock de Mexico, S.A. De C.V.  
Garlock New Zealand  
Garlock Great Britain Limited  
Garlock Middle East